

► TWF Paneles deslizantes

■ Paneles deslizantes

1	Panel cortante
2	Panel sobrepuesto

2

1



Elemento	Longitud del panel PL (m)	Altura del panel PH (m)	Espesor del panel PS (mm)	Longitud del tubo RDL (m)	Longitud del sistema SL (m)	Resistencia del sistema R_x (kN/m ²)	Peso (kg)
1	2,00	2,40	107	1,85	2,25 2,29*	220,2	575
2		1,40					367
1	2,44	2,40	107	2,29	2,69 2,73*	141,2	660
2		1,40					434
1	2,94	2,40	107	2,79	3,19 3,23*	97,9	828
2		1,40					521
1	3,52	2,40	107	3,37	3,77 3,81*	72,0	966
2		1,40					608
1	4,02	2,40	107	3,87	4,27 4,31*	55,1	1105
2		1,40					694
1	4,52	2,40	130	4,37	4,77 4,81*	78,5	1530
2		1,40					1010
1	5,02	2,40	130	4,87	5,27 5,31*	63,6	1788
2		1,40					1239
1	5,52	2,40	130	5,37	5,77 5,81*	52,6	1967
2		1,40					1200
1	6,02	2,40	130	5,87	6,27 6,31*	44,1	1980
2		1,40					1490
1	6,52	2,40	150	6,37	6,77 6,81*	45,0	2650
2		1,40					1810
1	7,02	2,40	150	6,87	7,27 7,31*	38,8	2850
2		1,40					1950

► Paneles REFORZADOS para SERVICIO PESADO bajo pedido