

► ABI Mobilram

■ TM 22

| Technical data | Unit | TM 22 |
|--|------------------|-----------------------------|
| Leader inclination front/rear | degree | 4/5 |
| Leader inclination laterally | degree | 4 |
| Leader slewing range | degree | +/- 95 |
| Stroke guiding carriage | mm | 22000 |
| Feed force mast cylinder 1 up / down | kN | 250 / 165 |
| Feed force mast cylinder 2 up / down | kN | 275 / 170 |
| Torque absorption max. | kNm | 200 |
| Load capacity | kg | 15000 |
| Winch hydraulically slewable and foldable (Option) | kN | 50 |
| Support cylinder (Option) | mm | 500 |
| Docking-System D6 | | |
| Connection for auger guide support integrated | | |
| Camera monitor system | | |
| Hydraulic extendable undercarriage T41/380-V | | |
| Attachments | | |
| VIBRATOR | MRZV 30/36 VV D6 | |
| AUGER DRIVE | MDBA 7000 D6 | |
| AUGER DRIVE | VDW 14070 D6 | |
| Gewichte / Maße | | |
| Operating Weight (with winch, with vibrator) | Kg | 83070 |
| Transport Weight (with winch and without attachment) | Kg | 77650 |
| Standard counterweight, detachable | Kg | 7 x 2450 |
| Base plate, detachable | Kg | 2100 |
| Transport dimensions | | |
| Length | mm | 14900 |
| Width | mm | 3000 |
| Height | mm | 3600 |
| BASE CARRIER | Unit | SR 35 F HD |
| ENGINE | CAT C18 | |
| Engine power | kW | 470 |
| Emissions standards | EU-Stufe/Stage V | |
| Working pressure | bar | 330 |
| Hydraulic pumps | cm ³ | 2 x 210 1 x 95 1 x 60 |
| Diesel tank | l | 810 |
| Track width | mm | 3500 |
| Track shoes | mm | 700 |

